

FEED TROLLEY KM143xxx Max. load 400kg

Konga Mekaniska Verkstad AB

Dång 2, SE 362 93 Tingsryd +46 (0)10-130 66 00, www.kongamek.se

Instructions.

Intended use.

The Feed trolley is designed to store / transport / lifting equipment in the industry, indoor and outdoor.

Inspection and maintenance. Feed trolley without lifting lugs.

Annual control feed trolley, that it is intact and that its wheels are firmly attached. Also check that the trolley is not exposed to abnormal wear and corrosive attacks.

Inspection and maintenance. Feed trolley with lifting lugs.

The trolley shall be controlled twice a year. Make sure that no notches or deformations occurred somewhere, special inspection of the lifting lugs and its fittings. At any deformation must not the trolley be used for any additional lifts. Also check that the trolley is not exposed to abnormal wear and corrosive attacks.

Feed trolley.



1) Feed trolley. 400 l. (200 l, 300 l.)

2) Lifting lugs x 4. Max load 400 kg. (Can be delivered without the lifting lugs)

3) Fixed castors x 2.

4) Swivel castors x 2. (Can be delivered with only one swivel castor.)



FEED TROLLEY KM143xxx Max. load 400kg

Declaration of conformity

Machinery Directive Annex 2A.

This declaration of conformity is only for the machine / product as it is supplied, not any additions or changes made by the customer / user.

Manufacturer: Konga Mekaniska Verkstad AB

Dång 2, SE 362 93 Tingsryd

+46(0)10-130 66 00 www.kongamek.se

Hereby declare that

Machine/Product: Feed trolley 400, 300, 200 litres.

Type: Feed trolley

No: KM143xxx + KM143000L

Meets the essential health and safety requirements of following directives and regulations:

Machinery directive 2006/42/EG.

According to Article 1: d) lifting accessories.

According to Article 5: d) Annex 2A.

Meets in full or in part the requirements of following standards and / or specifications. SS-EN 13155+A2:2009 (E).

Date: place: 2012-03-06 Konga

Signature:

Printed name: Paul Haglund